unit and a direct memory access unit coupled to an ATM slave processing unit, the interface unit comprising:

an input unit, the input unit receiving data cells and exchanging control signals with the ATM master processing unit;

an input buffer unit including:

a buffer storage unit; and

a calculation unit, wherein the input buffer unit receives data signals from and exchanges control signals with the input unit, the input buffer unit storing received data cells in the buffer storage unit, the buffer storage unit transferring data cells to the ~~ATM slave processing~~ direct memory access unit; and

a register, each data cell including a cell ~~location~~ portion ~~identifying a~~ having an encoded destination location, the calculation unit responsive to the contents of the register and to the ~~data~~ cell portion for generating a destination location ~~control signal~~ for the data cell in the ATM slave processing unit.

2. (Original) The interface unit as recited in claim 1 wherein the buffer storage unit is a first-in/first-out memory unit.

Please amend Claim 3 as follows.

3. (Currently Amended) The interface unit as recited in claim ~~1~~ 2 wherein the first-in/first-out memory unit can store at least two data cells.

4. (Original) The interface unit as recited in claim 1 wherein the buffer storage unit transfers a data cell to the slave data processing unit every clock cycle.

Please amend Claim 5 as follows.

5. (Currently Amended) The interface unit as recited in claim 1 wherein the destination locations can be selected from at least one of the group consisting of a ~~plurality of central~~ slave processing unit, a ~~plurality of~~ shared memory location for a plurality of slave processing units, and at least one ~~central~~ slave processing unit and at least one shared memory location.

Please amend claim 6 as follows.

6. (Currently Amended) The interface unit as recited in claim 1 further comprising:

an output buffer unit; the output buffer unit including a buffer storage unit, the buffer unit storing data cells, the output buffer unit receiving data cells from the ~~slave processing~~ direct memory access unit the data buffer unit exchanging control signals with the slave processing direct memory access unit; and

an output unit; the output unit receiving data cells from the output buffer unit and applying data cells to the ATM master processing unit, the output unit exchanging control signals with the output buffer unit and with the ATM master processing unit.

7. (Original) The interface unit as recited in claim 1 wherein the ATM slave processing unit includes at least one digital signal central processing unit.

Please amend Claim 8 as follows.

8. (Currently Amended) The interface unit as recited in claim 1 wherein the control signals and the data cells have ~~the~~ a UTOPIA format.

Please cancel Claim 9.

9. (Cancelled) The interface unit as recited in claim 1 wherein the ATM slave processing unit includes a direct memory access unit.

Please amend claim 10 as follows.

10. (Currently Amended) A method for exchanging data cells from an ATM master processing unit with a plurality of locations in an ATM slave processing unit, the ATM slave processing unit including a direct memory access unit, the method comprising:

storing data cells from the ATM master processing unit in a buffer storage unit;

comparing a field in the data cell with the contents of a register to determine the destination location of the data cell;

generating a signal identifying the destination location; and

when storage space is available, transferring a data cell from the buffer storage unit to the ~~destination location~~ direct memory access unit.

11. (Original) The method as recited in claim 10 further comprising:

implementing the buffer storage to hold two data cells; and

transferring a data cell from the buffer storage unit to the ATM slave processing unit on consecutive clock cycles.

12. (Original) The method as recited in claim 11 further comprising implementing the control signals in a UTOPIA format.

Please amend Claim 13 as follows.

13. (Currently Amended) The method as recited in claim 10 wherein ~~the ATM slave processing unit includes a direct memory access unit,~~ the method ~~including~~ includes applying the signal identifying the destination location to the direct memory access unit.

Please amend Claim 14 as follows.

14. (Currently Amended) A data processing system comprising:

an ATM master processing unit;

an ATM slave processing unit, the ATM slave processing unit including a direct memory access unit; and

an ATM slave interface unit, the slave interface unit including:

an input unit, the input unit receiving data signals from the ATM master unit, the input unit exchanging control signals with the ATM master unit;

an input buffer storage unit, the input buffer unit including:

a memory unit; and

a calculation unit, wherein the input buffer unit exchanges control signals with the input unit, the input buffer unit storing data cells in the memory unit, the buffer storage unit transferring data cells to the ATM slave processing unit, the input buffer unit exchanging control signals with the ~~ATM slave processing unit~~ direct memory access unit; and

a register, the contents of the register identifying ~~the~~ destination location field in a data cell, the contents of the register providing the translation of field in the data cell ~~to~~ into a destination location, wherein the calculation unit generates a destination location signal and applies the destination location signal to the ATM slave processing unit.

Please cancel Claim 15.

15. (Cancelled) The data processing system as recited in claim 14 wherein the ATM slave processing unit includes a direct memory access unit, the destination

location signal being applied to the direct memory access unit.

16. (Original) The data processing system as recited in claim 14 wherein the memory unit is a first-in/first-out memory unit capable of storing at least two data cells.

Please amend Claim 17 as follows.

17. The data processing system as recited in claim 16 wherein the input buffer unit transfers data cells to the ATM slave processing unit on consecutive ~~lock~~ clock cycles.

In the Specification

On Page 1, please delete the Paragraph after the title. Replace this Paragraph with the following Paragraph;

"This Application claims priority under 35 USC 119(e)(1) of Provisional Application Serial No. 60/237,237."

On Page 1, please delete the Paragraph entitled RELATED APPLICATIONS and replace this Paragraph with the following Paragraph.

"This Application claims priority under 35 USC 119(e)(1) of Provisional Application Serial No. 60/237,237 (TI-31779), titled APPARATUS AND METHOD FOR AN INTERFACE UNIT FOR DATA TRANSFER BETWEEN PROCESSING UNITS IN THE